

Premium Synthetic (PSY) Pool Quality Specifications

Quality Specifications for Component Streams to the Premium Synthetic (PSY) Pool								
Quality	Units	Min	Max	Typical*	Pool Typical Ex-Superior**	Referee Test Method	Test Frequency	Enbridge Response to Crude Not Meeting Quality
Existing Specifications								
Density (15C)	kg/m ³	>799	<876	830-876	863	ASTM D4052	Frequency: AR ²	Delayed shut-in ⁶
Viscosity	cSt	2	<20			ASTM D445	Frequency: QR ⁴	Delayed shut-in ⁶
Olefins, total ¹	wt%		<1			H NMR	Frequency: R ⁷	Immediate shut-in ⁵
Vapour Pressure (VPCR _{4.1} @ 37.8 C)	kPa		95,103 ⁸			ASTM D6377	Frequency: QR ⁴	Immediate shut-in ⁵
BS&W	vol%		0.5			ASTM D4007	Frequency: AR ²	Immediate shut-in ⁵
Organic Chlorides ¹	wppm		<1			ASTM D4929	Frequency: QR ⁴	Immediate shut-in ⁵
Component Typicals								
Sulphur, total	wt%			<0.2	0.1	ASTM D5453	Frequency: AR ²	Notification Process ⁶
Naphtha (IBP-350F)	mass% recovered			8-24	16	ASTM D7169	Frequency: MR ³	Notification Process ⁶
	mass% recovered			52-70	52	ASTM D7169	Frequency: MR ³	Notification Process ⁶
Distillate (350-650F)	mass% recovered			20-30	30	ASTM D7169	Frequency: MR ³	Notification Process ⁶
	mass% recovered			<1		ASTM D7169	Frequency: MR ³	Notification Process ⁶
Resid (+980F)	ppm			≤20		ASTM D5452-08		
Butane	vol%			≤3		ASTM D7169		
Other Requirements								
<ul style="list-style-type: none"> Stream must be produced by an Upgrader Cetane index in distillate: min 40 								

*The expected or anticipated crude quality of individual components, understanding the fact that there may be, on occasion, variability outside of the range of the typical.

**The estimated crude quality of a pool is based on a limited number of random composite samples of batches ex-Superior, timeframe July 2014 – March 2015.

***This specification was revised March 5th, 2014.

Notes

- For these properties, blending should not occur.
- AR: All Receipts of PSY component streams tested using weekly composite.
- MR: Monthly Random testing of PSY component streams.
- QR: Quarterly Random testing of PSY component streams. Upon violation perform probational testing at Enbridge discretion.
- Immediate shut-in upon identifying violation. Request third party Certificate of Analysis prior to subsequent receipt.
- Upon violation, notification to applicable party, increase monitoring. Consequence based on outcome of increased monitoring.
- R: Random testing. 2015 – Twice per year; 2016 onwards – Annually.
- Max 95kPa May 1st through Sept 15th
Max 103kPa Sept 16th through Apr 30th